

HOT VAPORCLEAN



Hot water (10 bar W.P. 30 bar B.P) and steam hose (6 bar W.P. 60 bar B.P.)

Standards: Phthalates free. FDA tit. 21 item 177.2600 aqueous and fatty foods. BfR XXI Cat.2 foods.

Application: softwall hose for delivery of hot water and steam used to wash down in dairies, slaughterhouses and in the food industry in general.

Temperature: -30°C +95°C hot water. -30°C + 165°C steam.

Construction

Tube: white, smooth, IIR rubber.

Reinforcement: high strength synthetic cord.

Cover: blue, smooth (wrapped finish), synthetic rubber, fatty food and weathering resistant.

Branding: continuous red stripe "IVG HOT (family logo)...".

Also available upon request: 1.Different diameters.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1465457	5	12/61	12	0,47	10	150	30	450	0,12	0,08	120	400
1465465	8	5/16	16,5	0,65	10	150	30	450	0,20	0,14	120	400
1300001	13	1/2	23	0,91	10	150	30	450	0,32	0,22	120	400
1464272	16	5/8	26	1,02	10	150	30	450	0,40	0,27	120	400
1461168	19	3/4	29	1,14	10	150	30	450	0,46	0,31	120	400
1461176	25	1	35	1,38	10	150	30	450	0,57	0,39	120	400