



STEAM VICTORIA LL



Steam hose for 210°C

Application: hardwall hose with steel cord reinforcement for saturated steam at a maximum working pressure 18 bar, used in the chemical industry, petrochemical and industrial applications in general, where a particular bending radius is necessary. Not recommended for steam cleaner. The hose can be used for peaks of superheated steam at 230°C and at 18 bar. Attention: the use of superheated steam reduces the hose life. For longer life drain after use.

Temperature: from -40°C (-40°F) to +210°C (+410°F).

Construction









Tube: black, smooth, EPDM rubber, resistant to saturated steam.

Reinforcement: inserts of steel wire and helix wire.

Cover: black, pin pricked, smooth (wrapped finish), EPDM rubber with excellent resistance to high temperatures, weathering, abrasion, and ageing.

Branding: continuous embossed marking "IVG Steam Victoria/LL...".

Also available upon request: 1. Different diameters.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
														
1256327	13	1/2	27,5	1,08	18	270	180	2700	0,74	0,50	84	3,3	60	200
1256343	19	3/4	33,5	1,32	18	270	180	2700	0,94	0,63	123	4,8	60	200
1231405	25	1	39,5	1,56	18	270	180	2700	1,24	0,84	162	6,4	60	200
1231430	32	1-1/4	48	1,89	18	270	180	2700	1,62	1,09	208	8,2	60	200
1231456	38	1-1/2	56	2,21	18	270	180	2700	2,18	1,46	247	9,7	60	200
1232541	51	2	69	2,72	18	270	180	2700	3,04	2,04	357	14,1	60	200
1265083	63,5	2-1/2	85,5	3,37	18	270	180	2700	4,61	3,10	444	17,5	60	200
1265180	76	3	98	3,86	18	270	180	2700	5,48	3,68	570	22,5	60	200