

## WATER MONTREAL 10



### Water discharge hose

**Application:** softwall discharge hose for water, non corrosive fluids and compressed air; used in construction sites, industries and agriculture.

**Temperature:** from -35°C (-31°F) to +70°C (+158°F).

**Construction**

**Tube:** black, smooth, synthetic rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

**Branding:** continuous green spiral stripe "IVG Water (family logo)...".

**Also available upon request:** 1. Different diameters 2. Yellow or blue hose cover 3. Different working pressures.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1015109	19	3/4	26	1,02	10	150	30	450	0,30	0,20	120	400
1015222	25	1	33	1,30	10	150	30	450	0,47	0,32	120	400
1015338	32	1-1/4	42	1,65	10	150	30	450	0,79	0,53	120	400
1143786	38	1-1/2	47	1,85	10	150	30	450	0,79	0,53	120	400
1457462	40	1-37/64	53,5	2,11	10	150	30	450	1,23	0,83	120	400
1088335	51	2	61	2,40	10	150	30	450	1,14	0,76	120	400
1119389	63,5	2-1/2	75,5	2,97	10	150	30	450	1,74	1,17	120	400
1143760	76	3	87	3,43	10	150	30	450	1,82	1,22	120	400
1101021	90	3-35/64	106	4,18	10	150	30	450	3,18	2,13	120	400
1141597	102	4	120	4,73	10	150	30	450	4,14	2,78	120	400