



VORTEX

VORTEX™ HIGH TEMPERATURE VACUUM QRC COUPLINGS WITH THREADED CONNECTION





VORTEX



VORTEX™ HIGH TEMPERATURE VACUUM QRC COUPLINGS WITH THREADED CONNECTION 1/4 ISO A

Vortex™ Vacuum QRC Couplings with threaded connections provide the high quality features of the **Vortex™** Coupling system with the flexibility of attaching to any threaded connection i.e. hose fittings, gauges, tooling etc.

Vortex™ Vacuum QRC Couplings are produced with a 1/4" BSP or NPT Female thread as standard and are temperature rated up to 250°C or 482°F.

Vortex™ Vacuum QRC Couplings parts are manufactured from high grade stainless steel, providing uniform expansion and contraction throughout the heat up and cool down cycle, removing the need for any secondary surface treatment process and providing a long working life.

All **Vortex™** QRC Couplings are fully serviceable and easy to maintain, servicing is carried out through the front face, without the need for removing the Coupling from the threaded connection.

A full range of **Vortex™** seal kits and spare parts are available from stock.



Premier Hose Technologies
Clifton Business Park,
Preston New Road, Clifton,
Preston PR4 0XQ, UK

Telephone +44 (1) 772 851370

sales@hosetechnologies.com

www.hosetechnologies.com

